

# ROYAL VAULT

# KINGDOM USA



Model RYV 6EW



Optional Electronic Lock

- *Six-Sided composite construction +2 hours fire protection*
- *A massive 7" thick door, 3" of solid barrier material*
- *Up to 7x2" chromed locking bolts*
- *Huge tempered glass protection with dual adjustable relocker*
- *Tri-spoke diecast handle with satin chrome finish*
- *Adjustable shelves*
- *Stainless steel facia plate*
- *Adjustable hinges with hardened bearings*

1st Security reserves the right to update products and/or make engineering or size changes without prior notice. All sizes and weights are approximate.



## SIX TIMES MORE PROTECTION



**1st**  
**SECURITY SAFE CO.**

901 South Hill, Los Angeles, CA 90015 U.S.A.  
PHONE: (213) 627-0422 FAX: (213) 627-8710  
E-mail: [info@firstsecuritysafe.com](mailto:info@firstsecuritysafe.com)  
Website: [www.firstsecuritysafe.com](http://www.firstsecuritysafe.com)

# ROYAL VAULT FIRE & BURGLARY TL-30×6

## “ Built To Last ”



Model Number	Outside Dimensions (H"×W"×D")	Inside Dimensions (H"×W"×D")	Cubic Foot Capacity	Weight (lbs)	# of Shelves	Door Swing Projections	Door Swing Projections (A)	Door Swing Projections (B)	Door Swing Projections (C)
RYV 3	36.5 × 26.5 × 31.5	30 × 20 × 21	7.3	1900	2		20"	46.5"	55.5"
RYV 4	51.5 × 30.5 × 31.5	45 × 24 × 21	13.1	2540	3		24"	55.5"	59.5"
RYV 5	61.5 × 30.5 × 31.5	55 × 24 × 21	16.0	3100	4		24"	55.5"	59.5"
RYV 6	66.5 × 26.5 × 31.5	60 × 20 × 21	14.6	2700	4		20"	53.5"	57.5"
RYV 6EW	66.5 × 40.5 × 31.5	60 × 34 × 21	24.8	3800	5		34"	74.5"	69.5"
RYV 7	71.5 × 34.5 × 31.5	65 × 28 × 21	22.1	3700	5		28"	59.5"	63.5"
RYV 8	74.5 × 42.5 × 36.5	68 × 36 × 26	36.8	4950	5		36"	78.5"	76.5"

When security greater than a TL30 Rated safe is required the Kingdom USA Royal Vault UL Rated TL-30×6 is the answer. Used world wide by jewelers and financial institutions for high level inventory storage and known for its superior construction, the Royal Vault is in a class of its own.

### LOCKS

Royal Vault safes are equipped with a UL listed group II key changeable combination lock. The lock is protected by a massive drill shattering hard plate and a punch resistant dial spindle is standard equipment on all Royal Vault safes.

### AUXILIARY LOCK

All Royal Vault TL-30×6 safes are equipped with a high security dual locking system. The auxiliary lock can function independently for daytime control or work together for dual protection of your valuables. Unlike most safes the Royal Vault TL-30×6 optional lock offers an additional spring loaded relock device protecting the lock further. Optional locks can be found in the following choice of configurations:

- Combination Lock along with Electronic Lock
- Combination Lock along with High Security Key Lock

### CONSTRUCTION

The Royal Vault is constructed of state of the art high density Agicrete monolith material encased within inner and outer magnesium steel hardplated on all 6 sides of the safe. The barrier material incorporates an unrivaled 26,000 PSI density and houses a matrix of nuggets and carbon fibers which further enhance its tensile strength. A reinforced armor plate protects the door frame and each individual bolt chamber from even the most sophisticated attack.

### PROTECTION

The Royal Vault's multiple 2" massive solid steel sliding bolts engage both vertically and horizontally into the body. In addition to the 6 sided protection, the Royal Vault features a huge floating glass plate "nerve center" that covers the entire lock area. Multiple auxiliary locks (relockers) are sensitized to engage if the nerve center is attacked. Standard equipment includes one sophisticated UL group 2M combination lock & one high security key lock.